

CLAIMS

SUBMIT

1. A downhole flow control device, comprising:  
2 a body defining a first passageway and a second passageway;  
3 a closure member moveable to selectively, substantially prevent flow through the first  
4 passageway; and  
5 a sleeve valve in the body positioned to control the flow through the second passageway.

1 N.E.

2. The device of claim 1, wherein the closure member is a plug.

1

3. The device of claim 1, wherein the closure member is a flapper valve.

1

4. The device of claim 3, wherein the flapper valve is controlled from the surface via a control line.

2

5. A downhole flow control device, comprising:  
2 a conduit defining a first bore therethrough and an annular space;  
3 the conduit further defining at least one second bore in the annular space;  
4 a sleeve member in the conduit selectively moveable to choke the flow through the  
5 second bore.

2

**1.**

2

**1**

1

1

1

Sub 111

13. A method of controlling fluid flow in a wellbore, comprising:

- 2 providing a body defining a first passageway;
- 3 blocking flow through the first passageway with a closure member;
- 4 directing fluid flow through a second passageway in the body around the closure
- 5 member; and
- 6 choking the flow through the second passageway.

14. A valve for use in a well, comprising:

- 2 a body defining a longitudinal first bore;
- 3 a closure member selectively positioned the first bore to block flow through a portion
- 4 thereof;
- 5 the closure member selectively removable from the first bore so that tools may be run
- 6 through the body past the closure member;
- 7 the body defining a second passageway communicating flow from a position upstream of
- 8 the closure member to a position downstream of the closure member to provide a
- 9 bypass flow;
- 10 a valve in the body moveable to selectively choke the bypass flow.

15. A valve for use in a well, comprising:

- 2 a choke controlling flow from a first end to a second end of the valve; and
- 3 a closure member providing selective access through the valve.

16. The valve of claim 15, further comprising:

52/11/17

3

a first conduit attached to a first end of the valve;

4

a second conduit attached to a second end of the valve; and

the valve choking the flow from the first conduit to the second conduit.

1

17. The valve of claim 15, wherein the choke comprises a sleeve valve.

1

18. The valve of claim 15, further comprising:

2

a first access bore through the valve;

3

the closure member providing selective access through the first access bore.

1

19. The valve of claim 15, further comprising:

2

a second flow bore through the valve providing a passageway through the valve that

3

bypasses the closure member.

1

20. A method of controlling fluid flow in a wellbore, comprising:

2

providing a valve having a closable access bore therethrough;

3

flowing fluid through the valve through a bypass passageway in the valve; and

4

providing a choke in the valve to selectively choke the fluid flow through the valve.